



## YIOZ.MH13503 Valves, Electrically Operated

[Page Bottom](#)

### Valves, Electrically Operated

[See General Information for Valves, Electrically Operated](#)

**ELSTER GMBH**

POSTFACH 2809

49018 OSNABRUECK, GERMANY

MH13503

Trademark and/or Tradename:  kromschroder

Safety shutoff valves "valVario" VA and VC series including the following types:

**Safety shutoff valves**, VAS followed by 1, 2 or 3, may be followed by T, followed by -, -0, 10, 15, 20, 25, 32, 40, 50 or 65, may be followed by a slash and -, -0, 10, 15, 20, 25, 32, 40, 50 or 65, followed N, followed by a slash, followed by N or L, followed by K, Q or W, may be followed by S or G, may be followed by R or L.

(When assembled as double block valve, the combinations of two VAS/VAS, VAS/VAG and VAS/VAD valves with one threaded inlet and one threaded outlet will be assembled together.)

VAS followed by 6, 7 or 8, may be followed by T, followed by 65, 80 or 100, followed by A, followed by 05, followed by a slash, followed by N or L, followed by K, Q or W, may be followed by S or G, may be followed by R or L, followed by B or E, may be followed by a slash and P, M, 1, 2, 3, 4, B, Z, V or -, may be followed by P, M, 1, 2, 3, 4 or -, may be followed by a slash and P, M, 1, 2, 3, 4, B, Z, V or -, may be followed by P, M, 1, 2, 3, 4 or -.

**Double block safety shutoff valve**, VCS followed by 6, 7 or 8, may be followed by T, followed by 65, 80 or 100, followed by A, followed by 05, followed by N or L, followed by N or L, followed by K, Q or W, may be followed by S or G, may be followed by R or L, followed by B or E, may be followed by a slash and P, M, 1, 2, 3 or 4, may be followed by P, M, 1, 2, 3 or 4, may be followed by P, M, 1, 2, 3, 4, B, Z, V or -, may be followed by P, M, 1, 2, 3, 4 or -, may be followed by a slash and P, M, 1, 2, 3 or 4, may be followed by P, M, 1, 2, 3 or 4, may be followed by P, M, 1, 2, 3, 4, B, Z, V or -, may be followed by P, M, 1, 2, 3, 4 or -.

**Safety valve with pressure reducing regulator**, VAD followed by 1, 2 or 3, may be followed by T, followed by -, 0, 10, 15, 20, 25, 32, 40, 50, 65, may be followed by a slash and 10, 15, 20, 25, 32, 40, 50, 65, - or -0, may be followed by N, followed by a slash, may be followed by N, followed by K, Q or W, may be followed by SL, GL, SR or GR, followed by -25, -50 or -100, followed by A or B.

**Safety shutoff valve with air/gas ratio regulator**, VAG followed by 1, 2 or 3, may be followed by T, followed by -, 10, 15, 20, 25, 32, 40, 50 or 65, may be followed by a slash and 10, 15, 20, 25, 32, 40, 50, 65, - or -0, may be followed by N, followed by a slash, may be followed by N, followed by K, Q or W, may be followed by SL, GL, SR or GR, followed by A or B, followed by E, K, A or N.

VAV followed by 1, 2 or 3, may be followed by T, followed by -, 10, 15, 20, 25, 32, 40, 50 or 65, may be followed by a slash and 10, 15, 20, 25, 32, 40, 50, 65, - or -0, may be followed by N, followed by a slash, may be followed by N, followed by K, Q or W, may be followed by SL, GL, SR or GR, followed by A or B, followed by E, K, A or N.

VAS = Safety shutoff valve

VCS = Combination of VAS

VCD = Combination of VAS and VAD

VCG = Combination of VAS and VAG

VCV = Combination of VAS and VAV

[Last Updated](#) on 2012-08-13

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2012 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.